



### Características Characteristics / Caractéristiques / Características

IP	20
Tensão (entrada) Voltage (Input) / Tension (Entrée) Tension (Entrada)	220V~240Vac
Frequência Frequence / Frequence Frecuencia	50/60Hz
Temperatura Temperature Température Temperatura	-25-85°C
Cor Colors / Couleurs / Colores	Alumínio, Branco Aluminum, White Aluminium, Blanc Aluminio, Blanco
Norma Norm / Norme / Norma	EN 61048 EN 61049



COD	REF	D (mm)	L (mm)	P (W)	EAN
0111280203	COND4,5UF	28	62	18/20/30/36/40	5604378150050
1001280030	COND6UF	28	62	70/75	5604378929618
0111280205	COND7UF	35	62	58	5604378150074
1471280013	COND8UF	35	62	50(HS) / 80(HM)	5604378691393
1001280021	COND9UF	35	62	125(HM)	5604378896675
1531280001	COND12UF	35	75	70(HS/Hi)	5604378726613
1001280020	COND20UF	35	95	150(HS/Hi)	5604378884115
1531280003	COND25UF	40	70	400(HM)	5604378726637
1531280004	COND32UF	42	79	250(HS/Hi)	5604378726644
1001280019	COND35UF	45	95	250(HS/Hi) / 400(HI)	5604378881190
1001280031	COND45UF	50	95	400(HS/Hi)	5604378960376
1001280032	COND60UF	45	103	1000(HM)	5604378960390